UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/676,429	09/30/2003	Bruce A. Phillips	020366-092300US	7056
	7590 10/03/201 nications International	EXAMINER		
1801 California	Street, # 900	RYAN, PATRICK A		
Denver, CO 80202			ART UNIT	PAPER NUMBER
			2427	
			MAIL DATE	DELIVERY MODE
			10/03/2011	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

		Application	plication No. Applicant(s)					
		10/676,42	29	PHILLIPS ET AL.				
	Office Action Summary	Examiner		Art Unit				
		PATRICK	A. RYAN	2427				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply								
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.  - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).								
Status								
1)  ズ	Responsive to communication(s) filed on 01 August 2011.							
2a)□								
	An election was made by the applicant in response to a restriction requirement set forth during the interview on							
٥,١	; the restriction requirement and election have been incorporated into this action.							
4)								
·/ <b>山</b>	closed in accordance with the practice under	•	•					
		-	,,					
Disposit	ion of Claims							
5)🛛	Claim(s) 1-55 is/are pending in the application	ion.						
	5a) Of the above claim(s) is/are withdrawn from consideration.							
6)	S) Claim(s) is/are allowed.							
7) 🔀	Claim(s) <u>1-55</u> is/are rejected.							
8)	Claim(s) is/are objected to.							
9)	Claim(s) are subject to restriction and/or election requirement.							
Application Papers								
10)□	The specification is objected to by the Exam	niner.						
11) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.								
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).								
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).								
12) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.								
Priority under 35 U.S.C. § 119								
•	•	ian priority un	Har 35     S.C. 8 110(a)	-(d) or (f)				
	13) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).							
a) ☐ All b) ☐ Some * c) ☐ None of:  1. ☐ Certified copies of the priority documents have been received.								
<ul><li>1. Certified copies of the priority documents have been received.</li><li>2. Certified copies of the priority documents have been received in Application No</li></ul>								
3. Copies of the certified copies of the priority documents have been received in this National Stage								
application from the International Bureau (PCT Rule 17.2(a)).								
* See the attached detailed Office action for a list of the certified copies not received.								
233 and alabelod detailed embe detail for a liet of the defined depice flot received.								
Attachment(s)								
1) Notice of References Cited (PTO-892)  4) Interview Summary (PTO-413)								
	ce of Draftsperson's Patent Drawing Review (PTO-948) rmation Disclosure Statement(s) (PTO/SB/08)		Paper No(s)/Mail Da 5) Notice of Informal P					
Paper No(s)/Mail Date 6) Other:								

Art Unit: 2427

## **DETAILED ACTION**

1. This Office action is made in response to Amendment and Remarks, filed August 1, 2011 ("Reply"). Applicant has amended Claims 1, 15, 27, 43, and 49. No claims have been added and no claims have been cancelled. As amended, Claims 1-55 are presented for examination.

2. In Office action of March 3, 2011 ("Office Action"):

Claims 1 through 55 were rejected under 35 U.S.C. 103(a) as being unpatentable over Zimmers et al. United States Patent (6,816,878 B1), hereinafter "Zimmers"; in view of Hunter et al. United States Patent (7,233,781 B2), hereinafter "Hunter"; view of Edson United States Patent (6,526,581 B1); in further view of Horvitz et al. United States Patent Application Publication (2003/0131142 A1) hereinafter "Horvitz".

### Continued Examination Under 37 CFR 1.114

3. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on August 1, 2011 has been entered.

Art Unit: 2427

# Response to Arguments

4. Applicant's arguments, see Reply Pages 15-19, have been fully considered, but are most in view of the new grounds of rejection.

### Claim Rejections - 35 USC § 103

- 5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6. Claims 1 through 55 are rejected under 35 U.S.C. 103(a) as being unpatentable over Zimmers et al. United States Patent (6,816,878 B1), hereinafter "Zimmers"; in view of Hunter et al. United States Patent (7,233,781 B2), hereinafter "Hunter"; in view of Edson United States Patent (6,526,581 B1); in further view of Austin-Lane et al. (US 2004/0044736 A1 "Austin").
- 7. In regards to Claims 15, Zimmers teaches a relationship between a telecommunication provider and a plurality of subscribers (network of computers connected by computer network connection 102, as shown in Fig. 1), a method for determining an appropriate set of addresses to which to distribute an alert (Fig. 4A through Fig. 4H), the method comprising:

maintaining a directory of alert gateways (Fig. 4B and Fig. 4E, as described in Col. 18 Lines 22-67 and Col. 20 Lines 1-14), the directory

comprising a plurality of directory entries (this limitations is met because multiple persons are intended to receive alert notifications, as disclosed in Zimmer Abstract and, therefore, a directory entry would be required for each user or household), each directory entry being associated with a particular alert gateway and comprising at least one gateway characteristic associated with that alert gateway (subscriber information table 184 of Fig. 3C with: Fields 200 - 206 ["alert gateway database entry"], such as, customer number, caller ID, Email, or IP address, and Fields 208 - 232 ["gateway characteristic"], such as ZIP code, latitude and longitude, or the special needs of a user), the gateway characteristic including information to enable the alert distribution device to determine whether a given alert should be transmitted to the alert gateway (Fields 208 - 232, as described in Col. 14 Lines 25-66);

maintaining a distribution address associated with each of the alert gateways, the distribution address for a particular alert gateway providing sufficient identifying information about that alert gateway to allow an alert to be transmitted to the alert gateway (Fig. 4B and Fig. 4E, as described in Col. 18 Lines 22-67 and Col. 20 Lines 1-14);

associating the at least one gateway characteristic for a particular alert gateway with the distribution address for that particular alert gateway (data describing the subscriber in elements 184, 186, 188, 190, 192, and 194 are commonly linked by customer number/identifier shown as elements 200, 260, 320, 330, 350, and 360 respectively. As described in Col. 14 Lines 3-24; these

Application/Control Number: 10/676,429

Art Unit: 2427

tables are generated using the processes of Fig. 4B and Fig. 4E, as described in Col. 18 Lines 22-67 and Col. 20 Lines 1-14);

Page 5

receiving an alert, the alert being configured to describe an event and having associated information about the alert comprising event information characterizing the event wherein said event information includes at least one of information related to an event category under which the event falls and information related to specific details about the event; (Figs. 4A, 4B, and 4D show the processes for receiving an alert notification from various sources. For example, from Emergency Managers Weather Information Network (EMWIN) of Fig. 4A, as described in Col. 17 Lines 53-67 and Col. 18 Lines 1-21; with additional reference to Fig. 2 showing additional information transmitted with the alert and Priority Level of the alert, as described in Col. 7 Line 9—Col. 8 Line 29);

identifying, based on the information about the alert, a set of selection criteria for determining which of the plurality of alert gateways should receive the alert (Fig. 4F, decision block 532 "Determine Type of Notification", as described in Col. 20 Lines 21-25; with further reference to the "patter matching and parsing" aspects of Fig. 4A, as described in Col. 18 Lines 4-21);

searching the directory for at least one directory entry comprising a gateway characteristic corresponding to the identified selection criteria (depending on the nature of the alert received, one of Figs. 5B, 6B, 7B, 8B, 9B, 10B, or 11 is performed in which a particular subscriber characteristic is use to determine if the alert should be sent to the individual, such as counties and zip

codes in reference to Fig. 5B. The act of searching needs to be performed in order to determine the subscribers who meet the selection criteria); and

identifying, based on the search, a set of at least one distribution address that should receive the alert, each member of the set of distribution addresses being associated with a directory entry comprising a gateway characteristic that corresponds to the identified selection criteria (step 620 database query system 112 retrieves all station identifiers of subscribers with matching criteria to the information contained in the alert);

Zimmers teaches distributing information about the alert to users of communication devices such as wired phones, cellular phones, fax machines, and computers within in a home or business setting (as discussed in Col. 4 Lines 17-60 and Col. 11 Lines 34-49). In addition, Zimmers discuses various modes of contact to provide alert information to users such as telephone number, e-mail address, or TCP/IP address (with reference to Col. 14 Lines 3-24). Zimmers also teaches a process of formatting data packets for distributing the alert one of the various user communication devices such as an Email Address at Step 574, a TCP/IP Address at Step 580, a Numeric Page at Step 586, or an Alphanumeric Pager at Step 592 (as shown in Fig. 4G and described in Col. 20 Line 66—Col. 21 Line 32). This contact information is organized into subscriber information table 184 of Fig. 3C with: Fields 200 - 206 ["alert gateway database entry"], such as, customer number, caller ID, Email, or IP address, and Fields 208 - 232 ["gateway characteristic"], such as ZIP code, latitude and longitude, or the special needs of a user, which are used to transmit targeted alerts to

the subscriber's location (Regions 140,142,144,146,148,150 of Fig. 1, as described in Col. 11 Line 10—Col. 12 Line 31).

However, within the teachings of Zimmers, it is unclear if the alert gateway is in communication with two or more types of subscriber equipment and is configured to analyze the alert and to determine to which of the two or more types of subscriber equipment to provide the alert as a function of analyzing the alert.

In a similar field of invention, Edson teaches a gateway device for an in-home communications network that utilizes several available in-home digital networking media to connect the gateway to device interfaces for communication with various external networks (Abstract, Fig. 1). Edson discloses various in-home devices connected to the Gateway 13 such as Audio System Component 34, Telephone 32, Printer 33, Alarm System 34, Appliance 41, TV 42, and Computer 43 (as shown in Fig. 1 and described in Col. 7 Line 35— Col. 9 Line 7). Furthermore, Edson's Gateway 13 interfaces with a number of external networks such as ADSL 15, CATV 17, and X-LINK 19 (as described in Col. 5 Lines 45-56). Edson additionally discloses that the Gateway 13 is capable of accommodating multiple sessions from multiple devices at the same time (with reference to Col. 6 Line 57—Col. 7 Line 9). Edson also discloses that Router 103, in conjunction with CPU 105, of Gateway 13 prioritizes and routs various communications between the internal device and between the devices and the external communication facilities (Col. 11 Lines 3-19).

Zimmers discloses distributing information about an alert to users of communication devices such as wired phones, cellular phones, fax machines, and

computers within in home or business locations. Edson demonstrates a need for a home network product that provides a simple common interface usable by a wide range of systems and appliances within the user's location (Col. 2 Line 64—Col. 3 Line 8). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the alert information distribution system of Zimmers with the home gateway device of Edson in order to increase the versatility and compatibility of alert distribution methods with various home electronic devices (as Edson suggests in Col. 2 Line 64—Col. 3 Line 8).

Edson does not explicitly discuss the reception of information about an alert from a distribution facility. In a similar field of invention, Hunter teaches a method and system for dissemination emergency notification information to a select subset of users based on the subject matter of the notification (Abstract). Hunter further describes the use of an Emergency Feedback and Notification (EFAN) System 100 and EFAN Device 110 (as generally shown in Fig. 2). As shown in Fig. 2, EFAN Device 110 can be located at Residential Homes 102 or Office Buildings 104 and can be embodied as a set-top box, as described in Col. 13 Lines 1-51. In addition, EFAN Device 110 functions as an alert gateway by only allowing the selection of messages, using message headers processed by Microprocessor 1108 of Fig. 4, that are intended for specific households to be displayed on subscriber equipment, such as TV Device 1103 of Fig. 3, as described in Col. 13 Line 52—Col. 14 Line 34; with further reference to Col. 3 Line 51—Col. 4 Line 44 and Col. 15 Lines 8-59.

The combination of Zimmers and Edson demonstrate a system for communicating information to multiple individuals who are using a variety of electronic devices. Hunter further demonstrates a need for a targeted dissemination of emergency information to differing geographic areas containing individuals with different personal needs or concerns (as disclosed in Col. 2 Lines 16-25). Therefore, one of ordinary skill in the art at the time of the invention would have been motivated to modify the gateway and routing device of Edson to transfer targeted alert information for reception on various electronic devices, such as the EFAN device of Hunter, in order to increase the versatility and compatibility of alert distribution methods with various home electronic devices (as Edson suggests in Col. 2 Line 64—Col. 3 Line 8 and as Hunter suggests in Col. 1 Line 28—Col. 2 Line 25).

Zimmers discloses distributing event information including event category of an alert to users of communication devices such as wired phones, cellular phones, fax machines, and computers within in home or business locations. Edson and Hunter teach local distribution of alert information to two or more types of subscriber equipment. However, the combination does not clearly demonstrate wherein the alert gateway is configured to analyze the event information and to determine to which of the two or more types of subscriber equipment to provide the alert as a function of analyzing the event information.

In a similar field of invention, Austin teaches a method and system for delivering an electronic notification to an intended recipient using a cascaded delivery technique including multiple diverse devices (Abstract, Paragraphs [0008-0009, 0021, 0029-

Art Unit: 2427

0032]). In particular, Austin teaches wherein the alert gateway is configured to analyze the event information and to determine to which of the two or more types of subscriber equipment to provide the alert as a function of analyzing the event information (operations of Notification Generation Service 349 including delivering notification according to notification triggers, as described in Paragraphs [0036-0048]; with further reference to the method of Fig. 8 including selecting an appropriate Delivery Mechanism 310 as a function of notification urgency, as described in Paragraphs [0075-0078]).

The combination of Zimmers, Edson, and Hunter teach a technique for distributing an alert to one of multiple devices by way of an alert gateway, where the receiving device is selected based on a transmission protocol. Austin teaches a technique for distributing an alert to one of multiple devices as a function of event information. It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the technique of Zimmers, Edson, and Hunter to allow for providing an alert as a function of analyzing event information, as described by Austin, in order to effectively distribute notifications to a user of multiple devices.

8. In regards to Claim 16, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the at least one gateway characteristic associated with each of the alert gateways comprises information about the geographic location of the alert gateway (selected data entries of Fig. 3C, such as Latitude, Longitude, Elevation, Postal Zip Code, or Physical Address, as described by Zimmers in Cols. 14-16 and Col. 17 Lines 1-52).

Application/Control Number: 10/676,429

Art Unit: 2427

9. In regards to Claim 17, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 16, wherein the information about the alert comprises geographic information about a geographic area to which the alert pertains, such that subscribers outside the geographic area would be relatively unlikely to be interested in receiving the alert (Zimmers teaches alert notification of Fig. 2, which contains county information 124 and town information 122, as described in Col. 8 Lines 42-67 and Col. 9 Lines 1-3).

Page 11

- 10. In regards to Claim 18, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the directory entry for each alert gateway comprises information about a distribution address for that alert gateway (Zimmers teaches subscriber information table 184 contains information regarding ANI (Caller ID), Email, and TCP/IP, which are associated with a telephone number, email address, or Internet Protocol address respectively), and wherein maintaining a distribution address associated with each of the alert gateways comprises maintaining the information about the distribution address (Zimmers Fig. 4B and Fig. 4E, as described in Col. 18 Lines 22-67 and Col. 20 Lines 1-14).
- 11. In regards to Claim 19, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the directory of alert gateways comprises a first database (Zimmers teaches tables of Fig. 3 are stored in database server 104, as disclosed in Col. 13 Lines 20-25).
- 12. In regards to Claim 20, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 19, wherein the distribution address associated with each of

Application/Control Number: 10/676,429

Art Unit: 2427

the alert gateways are maintained in a second database (Zimmers teaches database query system 112 generates packet data containing the information shown in TABLE III of Col. 12. The packet data is sent to an intended destination based on the "Station ID" and "Station ID Type", as described in Col. 12 Lines 32-67 and Col. 13 Lines 1-19).

Page 12

- 13. In regards to Claim 21, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the at least one gateway characteristic associated with an alert gateway comprises information selected from the group consisting of the area code in which the alert gateway is located, the ZIP code in which the alert gateway is located, the latitude and longitude coordinates of the alert gateway, the Global Positioning System coordinates of the alert gateway, demographic information about a subscriber associated with the alert gateway, and information about subscriber preferences held by a subscriber associated with the alert gateway (Zimmers teaches subscriber information table of Fig. 3C, as described in Cols. 14-16 and Col. 17 Lines 1-52).
- 14. In regards to Claim 22, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the alert comprises urgent public information (Zimmers discloses various applications of the alert system, some examples of which are disclosed in Col. 11 Lines 10-18).
- 15. In regards to Claim 23, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 22, wherein the urgent public information is selected from a group consisting of an Emergency Alert System transmission, an Amber Alert, a severe weather notification, and a Homeland Security Advisory notification (in addition to the

Art Unit: 2427

examples cited in reference to Claim 22, Zimmers teaches a specific application is shown in Fig. 2 regarding an alert sent by the National Weather Service (NWS), as described in Col. 8 Lines 30-67 and Col. 9 Lines 1-12).

- 16. In regards to Claim 24, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the information about the alert is incorporated within the alert (Zimmers teaches the alert transmitted from the NWS is transmitted using the ENWIN data stream, which is an alphanumeric text based system, as disclosed in Col. 8 Lines 30-41, so all information transmitted would be part of the data stream and therefore part of the alert).
- 17. In regards to Claim 25, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, wherein the alert information about the alert is additional to the alert (Zimmers teaches "the body of the NWS message may also be inserted into a facsimile message, sent as an electronic mail message, read via a computergenerated voice over the telephone, or forwarded to a text pager", as disclosed in Col. 9 Lines 4-7, these communications would require additional information to be added to the text data of the NWS data stream in order to be transmitted, for example, as an email notification).
- 18. In regards to Claim 26, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 15, further comprising extracting from the alert the information about the alert (Zimmers teaches data parsing process shown in Fig. 4A, as described in Col. 17 Lines 53-67 and Col. 18 Lines 1-21).

19. In regards to Claim 49, Zimmers teaches a relationship between a telecommunication provider and a plurality of subscribers (network of computers connected by computer network connection 102, as shown in Fig. 1), a method for determining an appropriate set of addresses to which to distribute an alert (Fig. 4A through Fig. 4H), the method comprising the steps addressed in Claim 15 and additionally:

the event including information about a geographic area to which the alert pertains, such that subscribers outside the geographic area would be relatively unlikely to be interested in receiving the alert (alert notification of Fig. 2, which contains county information 124 and town information 122, as described in Col. 8 Lines 42-67 and Col. 9 Lines 1-3); and

transmitting the alert to members of a set of distribution addresses (step 620 database query system 112 retrieves all station identifiers of subscribers with matching criteria to the information contained in the alert).

Zimmers teaches distributing information about the alert to users of communication devices such as wired phones, cellular phones, fax machines, and computers within in a home or business setting (as discussed in Col. 4 Lines 17-60 and Col. 11 Lines 34-49). In addition, Zimmers discuses various modes of contact to provide alert information to users such as telephone number, e-mail address, or TCP/IP address (with reference to Col. 14 Lines 3-24). Zimmers also teaches a process of formatting data packets for distributing the alert one of the various user communication devices such as an Email Address at Step 574, a TCP/IP Address at Step 580, a

Numeric Page at Step 586, or an Alphanumeric Pager at Step 592 (as shown in Fig. 4G and described in Col. 20 Line 66—Col. 21 Line 32). This contact information is organized into subscriber information table 184 of Fig. 3C with: Fields 200 - 206 ["alert gateway database entry"], such as, customer number, caller ID, Email, or IP address, and Fields 208 - 232 ["gateway characteristic"], such as ZIP code, latitude and longitude, or the special needs of a user, which are used to transmit targeted alerts to the subscriber's location (Regions 140,142,144,146,148,150 of Fig. 1, as described in Col. 11 Line 10—Col. 12 Line 31).

However, within the teachings of Zimmers, it is unclear if the alert gateway is in communication with two or more types of subscriber equipment and is configured to analyze the alert and to determine to which of the two or more types of subscriber equipment to provide the alert as a function of analyzing the alert.

In a similar field of invention, Edson teaches a gateway device for an in-home communications network that utilizes several available in-home digital networking media to connect the gateway to device interfaces for communication with various external networks (Abstract, Fig. 1). Edson discloses various in-home devices connected to the Gateway 13 such as Audio System Component 34, Telephone 32, Printer 33, Alarm System 34, Appliance 41, TV 42, and Computer 43 (as shown in Fig. 1 and described in Col. 7 Line 35— Col. 9 Line 7). Furthermore, Edson's Gateway 13 interfaces with a number of external networks such as ADSL 15, CATV 17, and X-LINK 19 (as described in Col. 5 Lines 45-56). Edson additionally discloses that the Gateway 13 is capable of accommodating multiple sessions from multiple devices at the same time (with

reference to Col. 6 Line 57—Col. 7 Line 9). Edson also discloses that Router 103, in conjunction with CPU 105, of Gateway 13 prioritizes and routs various communications between the internal device and between the devices and the external communication facilities (Col. 11 Lines 3-19).

Zimmers discloses distributing information about an alert to users of communication devices such as wired phones, cellular phones, fax machines, and computers within in home or business locations. Edson demonstrates a need for a home network product that provides a simple common interface usable by a wide range of systems and appliances within the user's location (Col. 2 Line 64—Col. 3 Line 8). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to combine the alert information distribution system of Zimmers with the home gateway device of Edson in order to increase the versatility and compatibility of alert distribution methods with various home electronic devices (as Edson suggests in Col. 2 Line 64—Col. 3 Line 8).

Edson does not explicitly discuss the reception of information about an alert from a distribution facility. In a similar field of invention, Hunter teaches a method and system for dissemination emergency notification information to a select subset of users based on the subject matter of the notification (Abstract). Hunter further describes the use of an Emergency Feedback and Notification (EFAN) System 100 and EFAN Device 110 (as generally shown in Fig. 2). As shown in Fig. 2, EFAN Device 110 can be located at Residential Homes 102 or Office Buildings 104 and can be embodied as a set-top box, as described in Col. 13 Lines 1-51. In addition, EFAN Device 110 functions

as an alert gateway by only allowing the selection of messages, using message headers processed by Microprocessor 1108 of Fig. 4, that are intended for specific households to be displayed on subscriber equipment, such as TV Device 1103 of Fig. 3, as described in Col. 13 Line 52—Col. 14 Line 34; with further reference to Col. 3 Line 51—Col. 4 Line 44 and Col. 15 Lines 8-59.

The combination of Zimmers and Edson demonstrate a system for communicating information to multiple individuals who are using a variety of electronic devices. Hunter further demonstrates a need for a targeted dissemination of emergency information to differing geographic areas containing individuals with different personal needs or concerns (as disclosed in Col. 2 Lines 16-25). Therefore, one of ordinary skill in the art at the time of the invention would have been motivated to modify the gateway and routing device of Edson to transfer targeted alert information for reception on various electronic devices, such as the EFAN device of Hunter, in order to increase the versatility and compatibility of alert distribution methods with various home electronic devices (as Edson suggests in Col. 2 Line 64—Col. 3 Line 8 and as Hunter suggests in Col. 1 Line 28—Col. 2 Line 25).

Zimmers discloses distributing event information about an alert to users of communication devices such as wired phones, cellular phones, fax machines, and computers within in home or business locations. Edson and Hunter teach local distribution of alert information to two or more types of subscriber equipment. However, the combination does not clearly demonstrate wherein the alert gateway is configured to analyze the event information and to determine to which of the two or more types of

subscriber equipment to provide the alert as a function of analyzing the event information.

In a similar field of invention, Austin teaches a method and system for delivering an electronic notification to an intended recipient using a cascaded delivery technique including multiple diverse devices (Abstract, Paragraphs [0008-0009, 0021, 0029-0032]). In particular, Austin teaches wherein the alert gateway is configured to analyze the event information and to determine to which of the two or more types of subscriber equipment to provide the alert as a function of analyzing the event information (operations of Notification Generation Service 349 including delivering notification according to notification triggers, as described in Paragraphs [0036-0048]; with further reference to the method of Fig. 8 including selecting an appropriate Delivery Mechanism 310 as a function of notification urgency, as described in Paragraphs [0075-0078]).

The combination of Zimmers, Edson, and Hunter teach a technique for distributing an alert to one of multiple devices by way of an alert gateway, where the receiving device is selected based on a transmission protocol. Austin teaches a technique for distributing an alert to one of multiple devices as a function of event information. It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the technique of Zimmers, Edson, and Hunter to allow for providing an alert as a function of analyzing event information, as described by Austin, in order to effectively distribute notifications to a user of multiple devices.

20. In regards to Claim 50, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 49, wherein at least one of the plurality of alert gateways is

incorporated within a network interface device located at a subscriber location (Router 103 of Edson, as shown in Fig. 2 and described in Col. 9 Line 51—Col. 11 Line 19).

Page 19

- 21. In regards to Claim 51, the combination of Zimmers, Edson, Hunter, and Austin teach the method of Claim 49, wherein at least one of the plurality of alert gateways is in communication with a network interface device located at a subscriber location (network interfaces 311-314 and 321-323 of Fig. 1, as further detailed in Fig. 4 and described in Col. 13 Line 17—Col. 14 Line 67).
- 22. The limitations of Claim 52 have been addresses with reference to Claim 49 and Claim 21.
- 23. The limitations of Claim 53 have been addresses with reference to Claim 49 and Claim 22.
- 24. The limitations of Claim 54 have been addresses with reference to Claim 49, Claim 22, and Claim 23.
- 25. In regards to Claim 1, Zimmers teaches a relationship between a telecommunication provider and a plurality of subscribers (network of computers connected by computer network connection 102, as shown in Fig. 1), a device for determining an appropriate set of addresses to which to distribute an alert (database query system 112, as described in Col. 11 Lines 27-33), the device comprising: at least one interface member in communication with a communication network (data base query system 112 is in communication with at least web server 114 and IVR system 116, as described in Col. 7 Lines 2-7, therefore database query system contains an IP

network interface); a processor in communication with the at least one interface member (database query system 112 may also "instruct web server 114 to deliver the alert notification", as disclosed in Col. 12 Lines 22-31); and a storage medium in communication with the processor (database query system 112 performs comparisons, such as that of Fig. 4F, which require known data, such as Table III, therefore database query system 112 must contain a storage medium), the storage medium comprising instructions executable by the processor to perform the method of Claim 15 (see the analysis of Claim 15 for references to these limitations).

- 26. The limitations of Claim 2 have been addresses with reference to Claim 1 and Claim 16.
- 27. The limitations of Claim 3 have been addresses with reference to Claim 1, Claim 16, and Claim 17.
- 28. The limitations of Claim 4 have been addresses with reference to Claim 1 and Claim 18.
- 29. The limitations of Claim 5 have been addresses with reference to Claim 1 and Claim 19.
- 30. The limitations of Claim 6 have been addresses with reference to Claim 1, Claim 19, and Claim 20.
- 31. The limitations of Claim 7 have been addresses with reference to Claim 1 and Claim 21.
- 32. The limitations of Claim 8 have been addresses with reference to Claim 1 and Claim 22.

- 33. The limitations of Claim 9 have been addresses with reference to Claim 1 and Claim 23.
- 34. The limitations of Claim 10 have been addresses with reference to Claim 1 and Claim 24.
- 35. The limitations of Claim 11 have been addresses with reference to Claim 1 and Claim 25.
- The limitations of Claim 12 have been addresses with reference to Claim 1 and 36. Claim 26.
- 37. In regards to Claim 13, the combination of Zimmers, Edson, Hunter, and Austin teach the device of Claim 1, wherein the communication network is selected from a group consisting of a radio-frequency transmission, a telephone network, a cable television distribution network, the Internet, a fiber-optic network, a high-speed data network, a wireless network, and a microwave network (Zimmers teaches in Fig. 1, alert notification system 100 consists of communication channels such as FM receiver 110, IP through web server 114, or public switched telecommunications network 136).
- 38. In regards to Claim 14, the combination of Zimmers, Edson, Hunter, and Austin teach the device of Claim 1, wherein the communication network is a plurality of communication networks and wherein, for a particular distribution address, the device is configured to select the most appropriate communication network via which to transmit the alert information to the particular distribution address (Zimmers teaches in Fig. 1, alert notification system 100 consists of communication channels such as FM receiver 110, IP through web server 114, or public switched telecommunications network 136.

Art Unit: 2427

In addition, database query system 112 can determine the appropriate transmission channel using the process of Fig. 4F, as described in Col. 20 Lines 15-65).

- 39. In regards to Claim 55, the combination of Zimmers, Edson, Hunter, and Austin teach the device of Clam 1, wherein the alert gateway transmits the alert to the subscriber equipment (as shown in Claim 15, Edson teaches Gateway 13 and Hunter teaches the distribution of alert information to subscriber equipment, namely EFAN Device 110).
- 40. In regards to Claim 27, Zimmers teaches a relationship between a telecommunication provider and a plurality of subscribers, a system for distributing an alert to an appropriate set of subscribers (alert notification system 100 of Fig. 1), the system comprising:

a communication network in communication with the plurality of subscribers (computer network connection 102, as described in Col. 6 Lines 36-67 and Col. 7 Lines 1-6); and an alert distribution device in communication with the communication network (database query system 112, as described in Col. 8 Lines 24-29), the alert distribution device comprising: at least one interface member in communication with the network; a processor in communication with the at least one interface member; and a storage medium in communication with the processor (the elements of database query system 112 have been addressed with reference to Claim 1), the storage medium comprising instructions executable by the processor to perform the method of Claim 49 (see the analysis of Claim 49 for references to these limitations).

Art Unit: 2427

41. The limitations of Claim 28 have been addresses with reference to Claim 27 and Claim 16.

- 42. The limitations of Claim 29 have been addresses with reference to Claim 27, Claim 16, and Claim 17.
- 43. The limitations of Claim 30 have been addresses with reference to Claim 27 and Claim 18.
- 44. The limitations of Claim 31 have been addresses with reference to Claim 27 and Claim 19.
- 45. The limitations of Claim 32 have been addresses with reference to Claim 27 and Claim 20.
- 46. The limitations of Claim 33 have been addresses with reference to Claim 27 and Claim 21.
- 47. The limitations of Claim 34 have been addresses with reference to Claim 27 and Claim 50.
- 48. The limitations of Claim 35 have been addresses with reference to Claim 27 and Claim 51.
- 49. The limitations of Claim 36 have been addresses with reference to Claim 27 and Claim 22.
- 50. The limitations of Claim 37 have been addresses with reference to Claim 27, Claim 22, and Claim 23.
- 51. The limitations of Claim 38 have been addresses with reference to Claim 27 and Claim 24.

- 52. The limitations of Claim 39 have been addresses with reference to Claim 27 and Claim 25.
- 53. The limitations of Claim 40 have been addresses with reference to Claim 27 and Claim 26.
- 54. The limitations of Claim 41 have been addresses with reference to Claim 27 and Claim 13.
- 55. The limitations of Claim 42 have been addresses with reference to Claim 27 and Claim 14.
- 56. In regards to Claim 43, Zimmers teaches a relationship between a telecommunication provider and a plurality of subscribers, a system for distributing an alert to an appropriate set of subscribers (alert notification system 100 of Fig. 1), the system comprising:

a network configured to provide communication with the plurality of subscribers (computer network connection 102, as described in Col. 6 Lines 36-67 and Col. 7 Lines 1-6); and an alert distribution device in communication with the communication network (database query system 112, as described in Col. 8 Lines 24-29), the alert distribution device comprising: at least one interface member in communication with the network; a processor in communication with the at least one interface member; and a storage medium in communication with the processor (the elements of database query system 112 have been addressed with reference to Claim 1), the storage medium comprising

instructions executable by the processor to perform the method of Claims 27 and 49 (see the analysis of Claims 27 and 49 for references to these limitations).

- 57. The limitations of Claim 44 have been addresses with reference to Claim 43 and Claim 34.
- 58. The limitations of Claim 45 have been addresses with reference to Claim 43 and Claim 35.
- 59. The limitations of Claim 46 have been addresses with reference to Claim 43 and Claim 22.
- 60. The limitations of Claim 47 have been addresses with reference to Claim 43, Claim 22, and Claim 23.
- 61. The limitations of Claim 48 have been addresses with reference to Claim 43 and Claim 21.

### Conclusion

62. Any inquiry concerning this communication or earlier communications from the examiner should be directed to PATRICK A. RYAN whose telephone number is (571)270-5086. The examiner can normally be reached on Mon to Thur, 9:00 am - 6:30pm EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Scott Beliveau can be reached on (571) 272-7343. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2427

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/P. A. R./ Examiner, Art Unit 2427 Wednesday, September 28, 2011

/Scott Beliveau/ Supervisory Patent Examiner, Art Unit 2427